

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
20 October 2005 (20.10.2005)

PCT

(10) International Publication Number  
**WO 2005/097377 A1**

(51) International Patent Classification<sup>7</sup>: **B22D 19/14**,  
17/20, 17/22, 19/00

(21) International Application Number:  
PCT/GB2004/003382

(22) International Filing Date: 12 August 2004 (12.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0408044.6 8 April 2004 (08.04.2004) GB

(71) Applicant (for all designated States except US): **COM-  
POSITE METAL TECHNOLOGY LTD** [GB/GB]; Grif-  
fith Building (A7), Cody Technology Park, Farnborough,  
Hampshire GU14 0LX (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BUSHBY, Roger,  
Stanley** [GB/GB]; 7 Roseberry Close, Basingstoke,  
Hampshire RG22 4XR (GB).


(74) Agent: **MAGUIRE BOSS**; 5 Crown Street, St. Ives, Cam-  
bridgeshire PE27 5EB (GB).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: LIQUID PRESSURE FORMING



(57) Abstract: A method of pressure forming a metal matrix composite (MMC), comprises: placing a fibre preform (not shown) into a die cavity (14) defined by a split die (12); introducing molten metal into the die cavity (14) through a sprue (16) to envelope the fibre preform; sealing the sprue (16); applying pressure direct to molten metal in the die cavity (14) with a mechanical compaction piston (18) to encourage infiltration of the fibre preform during solidification.

WO 2005/097377 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*